

Part No.

APGV-0000

APGV (300 psi / 20 bar) pump, 1/4" female NPT gauge swivel, 3ft hose, 1/4" MNPT process conn.

Quick and efficient pneumatic field testing of pressure transmitters, gauges or switches.



APGV-0000

Included Items

- Hand Pump - APGV Assembly (APGV)
- Hose - Quick-test 6900 psi hose, brass hose ends, 3 ft (92 cm) long (QTQT-HOS-3ft)
- Process Connection - 1/4" male NPT x male Quick-test, no check-valve, brass (QTHA-2MB0)
- Gauge Swivel - 1/4" Female NPT swivel, brass (SWIV-2FBW)

Specs/Attributes

Pressure Reference	None
Process Connection	1/4" Male NPT
Reference Connection	1/4" Female NPT
Max Pressure	300 PSI
Max Vacuum	0 In Hg
Materials	Aluminum, Brass, Plated Steel, Stainless Steel
Seal Materials	Buna-N, Delrin, Teflon
Min Temperature	0 °F
Max Temperature	130 °F

HISPACONTROL^{HC}
INSTRUMENTACION INDUSTRIAL

HISPACONTROL S.L.
 Pº Delicias 65 Bis
 28045 Madrid
 Tel. 915 308 552
hc@hispacontrol.com
www.hispacontrol.com